

**AMENDMENT TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-19 (Canceled)

Sub  
B1  
A1

20. (New) A pattern inspection apparatus for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data, said pattern inspection apparatus comprising:

- storage means for storing said reference pattern;
- inputting means for inputting said pattern image to-be-inspected;
- detecting means for detecting an edge of said pattern image to-be-inspected;
- inspecting means for inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern;
- and
- outputting means for outputting a result of said inspection.

21. (New) The pattern inspection apparatus as claimed in claim 20, wherein said detecting means detects the edge of said pattern image to-be-inspected with a sub pixel accuracy.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

22. (New) A pattern inspection apparatus for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data, said pattern inspection apparatus comprising:

storage means for storing said reference pattern;

inputting means for inputting said pattern image to-be-inspected;

inspecting means for inspecting said pattern to-be-inspected by comparing an edge of said pattern image to-be-inspected and an edge of said reference pattern;

and

outputting means for outputting a result of said inspection,

wherein said inspecting means conducts matching between said pattern image to-be-inspected and said reference pattern by comparing the edge of said pattern image to-be-inspected and the edge of said reference pattern.

23. (New) The pattern inspection apparatus as claimed in claim 22, wherein said matching is conducted by dilating the edge of said pattern image to-be-inspected or the edge of said reference pattern.

24. (New) The pattern inspection apparatus as claimed in claim 23, wherein said matching is conducted by dilating the edge of said pattern image to-be-inspected or the edge of said reference pattern with weightings given.

25. (New) The pattern inspection apparatus as claimed in claim 22, wherein said matching is conducted by using the total sum of products of amplitudes of the

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

edges of said pattern image to-be-inspected and amplitudes of the edges of said reference pattern at respective pixels as an evaluation value.

26. (New) The pattern inspection apparatus as claimed in claim 22, wherein said matching is conducted by calculating an evaluation value of the matching in consideration of a direction of the edge of said pattern image to-be-inspected and a direction of the edge of said reference pattern.

27. (New) The pattern inspection apparatus as claimed in claim 26, wherein said matching is conducted by using the total sum of inner products of edge vectors of said pattern image to-be-inspected and edge vectors of said reference pattern at respective pixels or the total sum of absolute values of said inner products as an evaluation value, wherein each of said edge vectors has a magnitude equal to amplitude of the edge and a direction identical to the direction of the edge.

28. (New) The pattern inspection apparatus as claimed in claim 22, wherein said matching is conducted by altering for each part of said reference pattern, a contribution thereof to the matching.

29. (New) The pattern inspection apparatus as claimed in claim 28, wherein said matching is conducted by extracting a unique pattern by using periodicity of said reference pattern, and setting different weightings for an evaluation value of the

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

matching depending on whether a pattern in said reference pattern is the unique pattern or not.

30. (New) A pattern inspection apparatus for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data, said pattern inspection apparatus comprising:

storage means for storing said reference pattern;

inputting means for inputting said pattern image to-be-inspected;

inspecting means for inspecting said pattern to-be-inspected by comparing an edge of said pattern image to-be-inspected and an edge of said reference pattern; and

outputting means for outputting a result of said inspection,

wherein said inspecting means assumes the correspondence of the edge of each pixel of said reference pattern to the edge of each pixel of said pattern image to-be-inspected.

31. (New) The pattern inspection apparatus as claimed in claim 30, wherein said correspondence-assumption is conducted considering the distance between the edge of each pixel of said reference pattern and the edge of each pixel of said pattern image to-be-inspected and the directional difference between both the edges.

32. (New) The pattern inspection apparatus as claimed in claim 30, wherein said inspecting means constructs an area based on the edges of said pattern image to-

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

be-inspected in which said inspecting means failed to assume said correspondence to the edges of said reference pattern, and recognizes said area as a defective area.

33. (New) The pattern inspection apparatus as claimed in claim 30, wherein said inspecting means constructs an area based on the edges of said pattern image to-be-inspected in which said inspecting means succeeded in assuming said correspondence to the edges of said reference pattern, detects an area whose luminance distribution is non-uniform among the areas, and determines said area as a defective area.

34. (New) The pattern inspection apparatus as claimed in claim 32 or 33, wherein said inspecting means judges a defect class based on geometrical feature quantities of said defective area.

35. (New) The pattern inspection apparatus as claimed in claim 32 or 33, wherein said inspecting means judges a defect class based on a feature quantity concerning the luminance of said defective area.

36. (New) The pattern inspection apparatus as claimed in claim 30, wherein said inspecting means calculates a pattern deformation quantity or pattern deformation quantities of said pattern to-be-inspected with respect to said reference pattern.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

37. (New) The pattern inspection apparatus as claimed in claim 36, wherein said pattern deformation quantity includes at least one of a displacement quantity, a magnification variation quantity, and a dilation quantity of the line width.

38. (New) The pattern inspection apparatus as claimed in claim 36, wherein said inspecting means adds an attribute of the pattern to said reference pattern.

39. (New) A pattern inspection apparatus for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data, said pattern inspection apparatus comprising:

- storage means for storing said reference pattern;
- inputting means for inputting said pattern image to-be-inspected;
- inspecting means for inspecting said pattern to-be-inspected by comparing an edge of said pattern image to-be-inspected and an edge of said reference pattern;

and

- outputting means for outputting a result of said inspection,

wherein said inspecting means forms a profile by examining luminance values in a profile acquisition section in said pattern image to-be-inspected, detects predetermined points for each said profile, approximates the detected points with a curve, and assumes the curve to be an edge of said pattern image to-be-inspected.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

40. (New) A pattern inspection method for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data, said pattern inspection method comprising:

- an inputting step of inputting said pattern image to-be-inspected;
- an detecting step of detecting an edge of said pattern image to-be-inspected;
- an inspecting step of inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern stored in storage means; and
- an outputting step of outputting a result of said inspection.

41. (New) A pattern inspection method for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data, said pattern inspection method comprising:

- an inputting step of inputting said pattern image to-be-inspected;
- an inspecting step of inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern stored in storage means; and
- an outputting step of outputting a result of said inspection,

wherein said inspecting step conducts matching between said pattern image to-be-inspected and said reference pattern by comparing the edge of said pattern image to-be-inspected and the edge of said reference pattern.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

42. (New) A pattern inspection method for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data, said pattern inspection method comprising:

an inputting step of inputting said pattern image to-be-inspected;

an inspecting step of inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern stored in storage means; and

an outputting step of outputting a result of said inspection,

wherein said inspecting step assumes the correspondence of the edge of each pixel of said reference pattern to the edge of each pixel of said pattern image to-be-inspected.

43. (New) A pattern inspection method for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data, said pattern inspection method comprising:

an inputting step of inputting said pattern image to-be-inspected;

an inspecting step of inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern stored in storage means; and

an outputting step of outputting a result of said inspection,

wherein said inspecting step forms a profile by examining luminance values in a profile acquisition section in said pattern image to-be-inspected, detects

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com



predetermined points for each said profile, approximates the detected points with a curve, and assumes the curve to be an edge of said pattern image to-be-inspected.

44. (New) A recording medium for recording a program that makes a computer execute a pattern inspection method for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data and capable of being read by the computer, said pattern inspection method comprising:

an inputting step of inputting said pattern image to-be-inspected;

an detecting step of detecting an edge of said pattern image to-be-inspected;

an inspecting step of inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern stored in storage means; and

an outputting step of outputting a result of said inspection.

45. (New) A recording medium for recording a program that makes a computer execute a pattern inspection method for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data and capable of being read by the computer, said pattern inspection method comprising:

an inputting step of inputting said pattern image to-be-inspected;

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

an inspecting step of inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern stored in storage means; and

an outputting step of outputting a result of said inspection,

wherein said inspecting step conducts matching between said pattern image to-be-inspected and said reference pattern by comparing the edge of said pattern image to-be-inspected and the edge of said reference pattern.

46. (New) A recording medium for recording a program that makes a computer execute a pattern inspection method for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data and capable of being read by the computer, said pattern inspection method comprising:

an inputting step of inputting said pattern image to-be-inspected;

an inspecting step of inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern stored in storage means; and

an outputting step of outputting a result of said inspection,

wherein said inspecting step assumes the correspondence of the edge of each pixel of said reference pattern to the edge of each pixel of said pattern image to-be-inspected.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

47. (New) A recording medium for recording a program that makes a computer execute a pattern inspection method for inspecting a pattern to-be-inspected by comparing an image of said pattern to-be-inspected with a reference pattern obtained from design data and capable of being read by the computer, said pattern inspection method comprising:

an inputting step of inputting said pattern image to-be-inspected;

an inspecting step of inspecting said pattern to-be-inspected by comparing the edge of said pattern image to-be-inspected and an edge of said reference pattern stored in storage means; and

an outputting step of outputting a result of said inspection,

wherein said inspecting step forms a profile by examining luminance values in a profile acquisition section in said pattern image to-be-inspected, detects predetermined points for each said profile, approximates the detected points with a curve, and assumes the curve to be an edge of said pattern image to-be-inspected.

48. (New) The pattern inspection apparatus as claimed in any one of claims 20, 22, 30, and 39, further comprising means for converting said design data into said reference pattern by correcting said design data with respect to deformation which may occur in said pattern to-be-inspected.

49. (New) The pattern inspection apparatus as claimed in any one of claims 20, 22, 30, and 39, further comprising means for setting allowable pattern deformation

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

Sub  
B  
1  
A

quantity and/or allowable pattern directional difference with respect to said reference pattern.

50. (New) The pattern inspection apparatus as claimed in claim 49, wherein said allowable pattern deformation quantity and/or said allowable pattern directional difference can be set individually in accordance with an attribute of said reference pattern.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com